

**1937 AUTOMOTIVE TIRE GAUGE**

Services all passenger cars. Four-sided nylon indicator bar is dual calibrated from 10 - 50 PSI (75 - 325 kPa). Anodized steel body with handy pocket clip. OAL: 6" (15cm).



**1933 DUAL FOOT TIRE GAUGE**

For use on dual wheels and other hard-to-reach valves. Four-sided nylon indicator bar is dual calibrated from 20 - 120 PSI (150 - 800 kPa). OAL: 6" (15cm)



**1935 HEAVY-DUTY DUAL FOOT TIRE GAUGE**

Extra-long gauge reaches inside and outside wheels. Built for use in heavy-duty environments. Two-sided nylon indicator bar is dual calibrated from 10 - 150 PSI (100 - 1,000 kPa). Includes hang-up ring. OAL: 12" (31cm)



**1929 DUAL FOOT AIR CHUCK EXTENSION**

Direct air line chuck for hard-to-reach valves on trucks, buses and tractors. 1/4" female NPT OAL: 6" (15cm)



**1931 BALL FOOT AIR CHUCK**

Direct air line chuck for standard applications. All brass construction with 1/4" female NPT and 3/4" hex drive.



**1925 4-WAY TIRE VALVE REPAIR TOOL**

Repairs and conditions inside and outside valve threads. Also removes and installs valve cores.



**A191 2-IN-1 TIRE INFLATOR & BLOW GUN**

Trigger-controlled air gun with 4" (102mm) offset nozzle allows user to inflate tires with air chuck end or blow air for cleaning etc. High-impact plastic handle features threaded brass insert for standard air lines. Maximum 180 PSI



**1990 BLOW GUN WITH 5 NOZZLES**

Versatile kit for a wide range of cleaning applications. Includes chrome-plated blow gun with rubber tip, long tapered nozzle, stubby tapered nozzle and two needle-nosed nozzles. Features hanging hook and vinyl coated lever. 1/4" NPT Female inlet.





### **1992 BLOW GUN WITH 2 NOZZLES**

Kit includes the two most popular nozzles: rubber tip and stubby tapered. Blow gun is chrome-plated and features hanging hook and vinyl coated lever. 1/4" NPT Female inlet.



### **1970 IN-LINE WATER SEPARATOR & AIR FILTER**

Attach to spray gun or air tool to remove water and filter out foreign particles. Features release valve for easy disposal. 1/4" x NPT Male inlet x 1/4" NPT Female outlet.



### **1975 AIR TOOL OILER**

Lubricate air tools, increasing both performance and life of tools. Attaches in-line to provide precise amount of oil, lubricating internal parts. For use with all 3/8" and 1/2" air tools. Inlet is 1/4" NPT Female, outlet is 1/4" NPT Male.



### **1972 AIR ADJUSTING VALVE**

Allows adjustment of spray gun air. Features dual-scale gauge (0 - 160 PSI and 0 - 11 kg/cm). Inlet is 1/4" NPT Male, outlet is 1/4" NPT Female.



### **1980 QUICK-CHANGE BACKING PAD**

6-1/2" diameter rubber pad fits most vertical and angle polishers. Includes 5/8" - 11 hex spindle nut for easy pad removal. 5,000 RPM maximum speed.



### **1982 QUICK-CHANGE SPRING CHISEL RETAINER**

For holding .401" shank chisels. Allows for quick and easy installation and removal.